

Telephone Tooless Keystone Jack

SKJ-213101

NOTES:

ELECTRICAL:

- 1.VOLTAGE RATING : 125V AC RMS
- 2.CURRENT RATING : 1.5 AMP
- 3.CONTACT RESISTANCE : 20 MILLIOHMS MAX
- 4.INSULATION RESISTANCE : 100 MEGOHMS MIN @ 500V DC
- 5.DIELECTRIC STRENGTH : 750V AC RMS 60Hz,1MIN

ENVIRONMENTAL:

- 1.STORAGE : -40° TO +70°
 - 2.OPERATION : -10° TO +60°
- CONFORM TO ANSI/TIA/EIA 568B CATEGORY 3
MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68,SUBPART F.

MECHANICAL:

1. HOUSING MATERIAL : PC
2. INSERT MATERIAL : PBT+30%GF
3. PCB MATERIAL : FR-4 THICKNESS:1.6mm
4. CONTACT MATERIAL : PHOSPHOR BRONZE STAMP PIN T=0.35mm
5. IDC CONTACT MATERIAL : PHOSPHOR BRONZE T=0.50mm WITH NICKEL PLATING
6. WIRE : AWG 22~24

PART NUMBER:SL3KJUT011103

